

# Medical Image-hased Diagnostics for



# Cardiovascular Discases Using Machine Learning

Alexander M. Martinez Lopez<sup>1,2</sup> | Carlos Gonzalez Rivera<sup>1,2</sup> Project Advisor: Dr. Edwin Florez, PhD<sup>1,2</sup>

Polytechnic University of Puerto Ricol Department of Biomedical Engineering<sup>2</sup>



### Abstract

With cardiac imaging's important role in the diagnosis of cardiac diseases, along with the dawn of big data and machine learning (ML), there are emergent opportunities to build AI tools that will directly assist physicians in heart failure (HF) diagnostics. An important application in biomedical engineering, as HF is very difficult to diagnose because of its complex symptoms, circumstance, and comorbidities. This study aims to: (1) perform accurate and precise cardiac segmentation and quantification of key left ventricle functional indices from CMR; and (2) build a ML tool using decision trees for image-based HF diagnosis. Quantification of left ventricular end-diastolic, end-systolic volumes and ejection fraction were achieved using Heron's formula and the area-length method. One-sample T tests revealed there were no statistical significance between the obtained mean values and the comparative mean values in each quantified variable. Statistical results show that quantified values of LV function closely resemble those established in the Sunnybrook Cardiac Data. Finally, a Machine Learning tool using decision trees for image-based heart failure diagnosis was successfully built, as every tested patient was classified correctly using the trained ML model.

### Introduction

Heart failure (HF) currently affects nearly five million Americans and contributes to approximately 287,000 deaths a year. HF is a chronic, progressive, and serious cardiovascular condition defined by the heart muscle being unable to pump enough blood to meet the body's needs for blood and oxygen. Despite being considered a major public health burden and the many recent advances in cardiovascular diagnosis and treatment, misdiagnosis is still a common concern for patients at risk of heart disease. Nowadays modern medical imaging techniques, such as magnetic resonance imaging (MRI) are widely used to assess qualitatively and quantitatively cardiac anatomical structures and functions<sup>2</sup>. Even with the incredible assessments medical images provide, HF patients are very difficult for physicians to diagnose correctly because they possess a variety of complex symptoms, circumstances, and comorbidities. Emerging disciplines like big data and machine learning (ML) have the potential to facilitate HF diagnosis with the use of artificial intelligence (AI) tools. Such AI image-based diagnostic tools have the potential to substantially alleviate the burden of HF through by providing fast and accurate diagnostic decision making.

### Objectives

The objectives of this research project are:


• Accomplish accurate and precise cardiac segmentation and quantification of left ventricular end-diastolic, end-systolic volumes and ejection fraction from CMR.

• Successfully build and evaluate a Machine Learning tool using decision trees for image-based heart failure diagnosis.

## Methodology



The Sunnybrook Cardiac Data (SCD) was utilized for thier CMR dataset.




SAX Basal slices and LAX 4-Chamber views, were utilized throughout the methodology.

Patient id..... SCD0000101 Modality..... MR Patient's Heart Rate..... 79 BPM Patient's Sex....: Relevant Image parameters Pixel Spacing....: [1.367188, 1.367188]

Slice Thickeness..: 10 mm Image Gap..... 10 mm Image size.....: 256 x 256, 131072 bytes


Relevant information from the image was extracted from the DICOM files.

The image's local features were enhanced using histogram equalization







Using Python's Skimage library endocardial LV boundaries were outlined using an active contour technique.



Ventricular length was determined from the apex to the mitral valve for end-diastole and end-systole.




Endocardial area is calculated using Heron's formula, to reduce geometrical assumptions.





method was the The area-length geometric approximation utilized to calculate the EDV and ESV of the LV.


Quantified data was utilized to train and test a decision tree ML model for HF diagnosis, using Python's Sklearn library.

The trained model classified the testing data as a binary output to "healthy" or "HF" patient.












Table1: Classification Test Metrics Healthy (0)

### Conclusions

Accurate and precise cardiac segmentation and quantification of LV functional indices from CMR was accomplished. Statistical results show quantified values closely resemble those established in the SDC. Finally, the AI HF diagnostics tool was successfully built, as every tested patient was classified correctly using the trained ML model.

### Future Work

An automatic segmentation methodology using ML should be implemented to reduce human inputs. Finally, additional input data regarding ethnicity, ventricular mass, electrocardiogram data and genetic data should be added to the ML model to become a viable assistance for physicians to rely on.

### References

- 1. Heart & Vascular: Conditions & Treatments.
- 2. Chen, C., Qin, C., Qiu, H., Tarroni, G., Duan, J., Bai, W., & Rueckert, D. (2020, February 17). Deep Learning for Cardiac Image Segmentation: A Review.

## Acknowledgements

We would like to express our deepest gratitude to Dr. Edwin Florez and the URP-HS committee for their motivating and valuable guidance during the project. We dedicate this project to our family and friends for their love and unconditional support through this step in our lives.